

商品仕様



Base model: MA70H/
R-8

● Type Name: MA70H/R

● Product Name : PC

● Presentation date :2001/05/10 ● Suggested retail price: ¥89,800
(minimum configuration, tax not included)

SPECIFICATIONS

| Item | | Item annotations | Specification |
|-------------------|--------------------------------|--------------------|--|
| CPU | | | Celeron(TM) Processor |
| Clock frequency | | | 700MHz |
| Cached memory | 1st time | | 32KB (with built-in CPU) |
| | 2nd time. | | 128KB(CPU built-in) |
| Bus Clock | System Bus | | 66MHz |
| | Memory bus | | 100MHz |
| Chipset | | | Intel® 810E Chipset |
| Memory (main RAM) | Standard capacity | | 64MB (minimum configuration) |
| | Number of slots | | DIMM Slots x 2 |
| | Maximum capacity | *36 | 256MB |
| Display function | Video RAM | | 7 - 12 MB (main memory) |
| | Graphic accelerators | | Built-in Intel(R) 810E Chipset |
| | Resolution and display color | 640 × 480 dots | *3*20 Up to 1,677 million colors |
| | | 800 x 600 dots | *3*20 Up to 1,677 million colors |
| | | 1,024 × 768 dots | *3*20 Up to 1,677 million colors |
| | | 1,280 x 1,024 dots | *3*20*28 Up to 1,677 million colors |
| | | 1,600 x 1,200 dots | *3*20*28 Up to 256colors |
| Sound function | Sound source/Surround function | | Built-in PCM recording playback function, stereo, quantization 8-bit / 16-bit, full-duplex (mono, 8-Quantization), sampling rate (8-48KHz) |
| | Speaker | | -*4 |
| Floppy disk drive | | *19 | 3.5-inch floppy disk drive (compatible with 3modes) |

| | | | |
|--|-----------------------------------|------|---|
| Slots | PCI | * 10 | 3 slots (full x 2, half x 1, half x 1, half slot occupied by LAN / fax modem *11 [Available slots 2] |
| Interface | USB | | 2 (Main body front × 1, back of main body × 1) |
| | Parallels | *15 | D-sub25 pin |
| | Serial | *15 | D-sub9 pin |
| | Display (Analog) | | Mini D-sub15 pin |
| | PS/2 | *21 | Mini DIN 6 pin x 2 [Ps/2 connection keyboard selection, occupied by keyboard and mouse] |
| | Fax Modem | | RJ11 Modular connector (when fax modem is selected) |
| | Lan | | RJ45 (100BASE-TX/10BASE-T) LAN connector (when LAN is selected) |
| Sound related interface | Line input | | Stereo Mini Jack |
| | Line output | | Stereo Mini Jack |
| | Microphone input | | Mono-Mini Jack |
| Bay | | | 3.5 type bay: 1 slot (Occupied with FDD) [Available with FDD], 5-type Bay: 2-slot (one-slot occupied by CD-ROM or CD-RW) [Available Slots 1], Built-in 3.5-inch Bay: 2-slot (one-slot occupied by standard HDD) [Available Slots 1] |
| Power | | | AC100V ± 10%, 50/60Hz |
| Power consumption | Standard | *7 | About 26W |
| | Maximum | *7 | About 169W |
| Energy consumption efficiency | | *7 | R Segments 0.012 |
| Countermeasures against radio interference | | | VCCI Class B |
| Temperature and humidity conditions | | | 10 - 35° C, 20 - 80% (but no condensation) |
| External dimensions | Main body (excluding protrusions) | | 181(W) × 389(D) × 363(H)mm |
| Mass | Main body | *7 | About 10.5Kg |
| Selection menu | | | Click here for more information on the selection menu |
| Additional information | | | [Main Attachments]: Manual, Power Cable, Warranty, Ground Wire, Backup CD-ROM*18 |

The above is the specification of the main body hardware, and depending on the operating system and application, it may not support the functions of the above hardware. Please refer to the Selection Menu Table for type names and model numbers in the selected selection menu.

*3: The resolution and color count of the PC itself are the ability of the computer body, and depending on the display to be connected, it may not be displayed.

*4: External speaker is required for sound source playback. (Main unit line output terminal use)

*7: Windows(R) 2000 Professional (Microtower type is Windows(R) Millennium Edition), minimum capacity memory (maximum capacity energy consumption efficiency), minimum capacity HDD (mass maximum capacity), LAN, CD-ROM (no model without model), FDD (no model without model), USB109 keyboard (microtower type PS/2 109 keyboard),

*10: Depending on the configuration you choose, you may use free slots.

*11: LAN board or fax modem board cannot be removed.

*15: Parallel/serial ports may be required for operating environments depending on the software used.

*18: Backup CD-ROM is a batch re-setup method.

*19: Supports 3 modes (720KB, 1.2MB, 1.44MB). In addition, support for 1.2MB in Windows (R) Millennium Edition and Windows (R) 2000 Professional requires driver setup (standard attachment). In addition, 1.2MB is not formatable on Windows (R) Millennium Edition and Windows (R) 98 Second Edition.

*20: When using Windows(R) Millennium Edition, a display with a display resolution of 800 x 600 dots or more is required during setup.

*21: If you select a USB-connected keyboard on the Windows NT(R) 4.0 model, you cannot connect the PS/2 mouse or the PS/2 keyboard.

*28: Space-saving, desktop, and mini-tower MA10T/M cannot be displayed when a digital LCD is connected.

*36: Some selection menu of the main RAM requires the memory that is standard implemented to be removed.